Whenever there is limited space in an entrance an electric sliding gate which takes up little or no room is the ideal solution.



AC Sliding Gate Motor

Smooth & Quiet

Gearmotors in oil bath

Anti-Crushing Safety Device

Dual-disc clutch - present for inductive sensor

Simplicity

Manual maneuver unlocking with customized key

Safety, Precision & All Weather Conditions

Magnetic Limit switch

Solodity, Robustness & Durability

Anodized die cast aluminium block gearmotor Unit With hardened steel gears

Fixing

Practical with screws and bolts plate exterior





SPECIFICATION

MODEL	SL-2200	SL-1800
Power Supply / Frequency	AC220 + 10% 50Hz	AC220 + 10% 50Hz
mechanical Movement	OilBath	Grease
Motor Rating Power	370W	370W
Environment Temperature	-40°C ~ +70°C	-40°C ~ +70°C
Max. Gate Weight	1600 kgs	800 kgs
Output Torque	≥22Nm	≥22Nm
Opening Speed	12m/min	12m/min
Protection Rating	IP44	IP44
Capacitor	20°F	20°F
Pinion Gear	Z19	Z19
Net Weight	16kgs	12kgs
Key-release Mechanical	Yes	Yes
Adjustable Clutch	Yes	No