

CA-6 INTRUDER ALARM CONTROL PANEL

CA-6 is an intruder alarm control panel which is simple to install and use, and provides high security to small and medium premises. This panel is flexible to program, which makes it ideal for installation in specific applications.

- up to 8 zones:
 - support for NC, NO, EOL, 2EOL/NC and 2EOL/NO loop configurations
 - flexible selection of zone function
- 5 programmable outputs
- 2 partitions
- RS-232 TTL port for local upload/download – RJ type socket
- on-board PSTN telephone dialer for reporting, messaging and remote uploading/downloading
- system operation:
 - LED keypad
 - remote operation by telephone (with optional **MST-1** module)
- system programming:
 - local (LED keypad, PC (using the **DLOAD10** program) connected to RS-232 port)
 - remote (PC communicating via modem)
- system codes:
 - 1 master user code
 - up to 12 user codes
 - 1 service code
 - an option to define system access authority for the codes
- 4 timers
- event log with 255 entries
- monitoring using Contact ID and other protocols:
 - 2 monitoring stations numbers
- messaging:
 - 4 telephone numbers
 - 1 voice message
 - 2 text messages
- incoming call answering
- advanced telephone tone analysis:
 - TBR-21 compliant tone detection
 - intelligent redial attempts
 - programmable dialing sequence
- built-in 300 bps modem
- auto-diagnostic features for basic system components
- on-board switching mode power supply



CA-6 KLED-S

LED keypad for CA-6

- LEDs for zones, partition and system state indication
- keypad hold-down PANIC, FIRE and AUX alarms
- keypad backlight
- buzzer for acoustic signaling
- two zones expansion
- communication loss indication



CA-6 KLED-S

CA-6 KLED

LED keypad for CA-6

- LEDs for zones, partition and system state indication
- keypad hold-down PANIC, FIRE and AUX alarms
- keypad backlight
- buzzer for acoustic signaling
- two zones expansion



CA-6 KLED